

MATERIAL TESTING LABORATORY

MILITARY ENGINEER SERVICES (MES) TEST RESULTS FOR FINENESS MODULUS (F.M.) OF SAND

Job No : 218/2018-2019 (Sand).

Name of Client : GE(Navy) Dhaka. Copy No : 01

Ref Itr No : CEN/91 of 2017-2018/19/E-2 Dt. 25 April 2019.

Project Name : CEN/91 of 2017-2018.

Sample Specimen : Sylhet Sand.

Date of Sample Collection : Sunday, 05 May, 2019

Sieve Size	Wt of Material Retained (gms)	Percentage Matarial Retained (rounded)	Cumulative % Retained	% Finer	Remarks
#4	1.14	0.29	0.29		
#8	13.55	3.39	3.67		
#16	69.56	17.39	21.06		
#30	189.55	47.39	68.45		
#50	106.69	26.67	95.12		FM = 2.88
#100	15.99	4	99.12		
#200	3	0.75	••••		
Pan	1	0.25			
			$\Sigma = 287.71$		

Cautions:

- 1. Samples as supplied to the laboratory have been tested. The laboratory authority does not bear any responsibility as to the representative charecter of the samples to be tested.
- 2. It is recommended that the samples are sent in a secured and sealed cover/packet/container under signature of the competent authority.
- 3. In order to avoid fraudulent fabrication of the test results, it is recommended that all test reports should be collected by duly authorized person and not by the contractor/supplier.

Observation on Specimen(if any):

1. 2.

Laboratory Technichian

Test Performed By

Vetted By

This is a computer genarated copy

No signature is required

Permissible Value:

- 1.For Sylhet/Domar Sand minimum FM will be = 2.50
- 2.For Local Sand minimum FM will be = 1.50
- 3. For Vitty Sand minimum FM will be = 0.80