

MATERIAL TESTING LABORATORY

MILITARY ENGINEER SERVICES (MES) TEST RESULTS FOR FINENESS MODULUS (F.M.) OF SAND

Job No : 30/19-20(Sand)

Name of Client : AGE(Army) Momenshahi. Copy No : 1

Ref Itr No : CEA/392 of 2018-2019/08/E-6 Dt. 23 July' 2019.

Project Name : CEA/392 of 2018-2019.

Sample Specimen : Sylhet sand

Date of Sample Collection : Wednesday, 24 July, 2019

Sieve Size	Wt of Material Retained (gms)	Percentage Matarial Retained (rounded)	Cumulative % Retained	% Finer	Remarks
#4	0	0	0		
#8	14.65	3.66	3.66		
#16	148.65	37.16	40.83		
#30	186.07	46.52	87.34		
#50	48.48	12.12	99.46		FM = 3.31
#100	2	0.5	99.96		
#200	0	0			
Pan	0	0			
			$\Sigma = 331.26$		

Cautions:

- 1. Samples as supplied to the laboratory have been tested. The laboratory authority does not bear any responsibility as to the representative charecter of the samples to be tested.
- 2. It is recommended that the samples are sent in a secured and sealed cover/packet/container under signature of the competent authority.
- 3. In order to avoid fraudulent fabrication of the test results, it is recommended that all test reports should be collected by duly authorized person and not by the contractor/supplier.

Observation on Specimen(if any):

1.

2.

Laboratory Technichian Test Performed By Vetted By

This is a computer genarated copy

No signature is required

Permissible Value:

- 1.For Sylhet/Domar Sand minimum FM will be = 2.50
- 2.For Local Sand minimum FM will be = 1.50
- 3. For Vitty Sand minimum FM will be = 0.80