

MATERIAL TESTING LABORATORY

MILITARY ENGINEER SERVICES (MES) TEST RESULTS FOR FINENESS MODULUS (F.M.) OF SAND

Job No : 108/2019-2020(Sand)

Name of Client : AGE(Air) Cox's Bazar. Copy No : 02

Ref Itr No : CE(Air)/227 of 2017-2018/15/E-6 Dt.04 Sept'2019

Project Name : CE(Air)/227 of 2017-2018

Sample Specimen : Local sand.

Date of Sample Collection : Thursday, 05 September, 2019

Sieve Size	Wt of Material Retained (gms)	Percentage Matarial Retained (rounded)	Cumulative % Retained	% Finer	Remarks
#4	0	0	0		
#8	4	1	1		
#16	34.13	8.53	9.53		
#30	60.1	15.03	24.56		
#50	199.61	49.9	74.46		FM = 2.06
#100	89.43	22.36	96.82		
#200	8.65	2.16			
Pan	3.7	0.93			
			$\Sigma = 206.37$		

Cautions:

- 1. Samples as supplied to the laboratory have been tested. The laboratory authority does not bear any responsibility as to the representative charecter of the samples to be tested.
- 2. It is recommended that the samples are sent in a secured and sealed cover/packet/container under signature of the competent authority.
- 3. In order to avoid fraudulent fabrication of the test results, it is recommended that all test reports should be collected by duly authorized person and not by the contractor/supplier.

Observation on Specimen(if any):

1. 2.

Laboratory Technichian

Test Performed By

Vetted By

This is a computer genarated copy

No signature is required

Permissible Value:

- 1.For Sylhet/Domar Sand minimum FM will be = 2.50
- 2.For Local Sand minimum FM will be = 1.50
- 3. For Vitty Sand minimum FM will be = 0.80