

MATERIAL TESTING LABORATORY

MILITARY ENGINEER SERVICES (MES) TEST RESULTS FOR FINENESS MODULUS (F.M.) OF SAND

Job No : 198/19-20(Sand).

Name of Client : GE (Air) Chattogram. Copy No : 01

Ref Itr No : CE(Air)/71 of 2018-2019/12/E-6.Dt 18 Nov 2019.

Project Name : CE(Air)/71 of 2018-2019.

Sample Specimen : Sylhet Sand.

Date of Sample Collection : Wednesday, 20 November, 2019

Sieve Size	Wt of Material Retained (gms)	Percentage Matarial Retained (rounded)	Cumulative % Retained	% Finer	Remarks
#4	4.82	1.21	1.21		
#8	20.5	5.13	6.33		
#16	53.54	13.39	19.72		
#30	77.33	19.33	39.05		
#50	191.73	47.93	86.98		FM = 2.52
#100	46.64	11.66	98.64		
#200	4.3	1.08			
Pan	1.11	0.28			
			$\Sigma = 251.92$		

Cautions:

- 1. Samples as supplied to the laboratory have been tested. The laboratory authority does not bear any responsibility as to the representative charecter of the samples to be tested.
- 2. It is recommended that the samples are sent in a secured and sealed cover/packet/container under signature of the competent authority.
- 3. In order to avoid fraudulent fabrication of the test results, it is recommended that all test reports should be collected by duly authorized person and not by the contractor/supplier.

Observation on Specimen(if any):

1. 2.

Laboratory Technichian

Test Performed By

Vetted By

This is a computer genarated copy

No signature is required

Permissible Value:

- 1.For Sylhet/Domar Sand minimum FM will be = 2.50
- 2.For Local Sand minimum FM will be = 1.50
- 3. For Vitty Sand minimum FM will be = 0.80