

## MATERIAL TESTING LABORATORY

# MILITARY ENGINEER SERVICES (MES) TEST RESULTS FOR FINENESS MODULUS (F.M.) OF SAND

Job No : 253/19-20 (Sand).

Name of Client : AGE (Army) Momenshahi. Copy No : 01

Ref Itr No : CEA /659 of 2018-2019/24/E-6.Dt 26 Jan' 2020.

Project Name : CEA /659 of 2018-2019.

Sample Specimen : Local sand.

Date of Sample Collection : Monday, 27 January, 2020

Sieve Size	Wt of Material Retained (gms)	Percentage Matarial Retained (rounded)	Cumulative % Retained	% Finer	Remarks
#4	0	0	0		
#8	2.3	0.58	0.58		
#16	12.72	3.18	3.76		
#30	45.64	11.41	15.17		
#50	224.82	56.21	71.37		FM = 1.9
#100	109.11	27.28	98.65		
#200	5.05	1.26	<b></b>		
Pan	0.24	0.06			
			$\Sigma = 189.51$		

#### **Cautions:**

- 1. Samples as supplied to the laboratory have been tested. The laboratory authority does not bear any responsibility as to the representative charecter of the samples to be tested.
- 2. It is recommended that the samples are sent in a secured and sealed cover/packet/container under signature of the competent authority.
- 3. In order to avoid fraudulent fabrication of the test results, it is recommended that all test reports should be collected by duly authorized person and not by the contractor/supplier.

# **Observation on Specimen(if any):**

1.

2.

Laboratory Technichian Test Performed By Vetted By

This is a computer genarated copy

No signature is required

### Permissible Value:

- 1.For Sylhet/Domar Sand minimum FM will be = 2.50
- 2.For Local Sand minimum FM will be = 1.50
- 3. For Vitty Sand minimum FM will be = 0.80