

MATERIAL TESTING LABORATORY

MILITARY ENGINEER SERVICES (MES)

TEST RESULTS FOR COMPRESSIVE STRENGTH OF CONCRETE CYLINDER/CUBE

Job No : 832/19-20(Con).

Name of Client : AGE (Air) Cox's bazar. Copy No. : 02

Ref Itr No : CE (Air)/227 of 2017-2018/46/E-6.Dt 29 Jan 2020. Sample Specimen : HT 200mm (8"), Dia 100mm (4")

Project Name : CE (Air)/227 of 2017-2018. Type of Aggregate : Stone

Status of Sample : 1st floor roof. Brand & Type of Cement : Diamond opc.

Date of Collection : Thursday, 30 January, 2020 Proportion of Mixture : 1:1.5:3

Test Standard : ASTM/BS Desired Design Strength : 3500 psi

Ser No	Date of Casting and (Age in days)	Date of Test	Specimen Area Sq inch	Maximum Load (Lbs.)	Crushing Strength (psi)	Average Crushing Strength (psi)	Type of Failure
1			12.17	12485	1026		
2	26-Jan-20 (28 days)	23-Feb-20	12.17	10946	899	993	Aggregate/ Morter or Both Failure
3			12.17	12827	1054		

Cautions:

- 1. Samples as supplied to the laboratory have been tested. The laboratory authority does not bear any responsibility as to the representative charecter of the samples to be tested.
- 2. It is recommended that the samples are sent in a secure and sealed cover/packet/container under signature of the competent authority.
- 3. In order to avoid fraudulent fabrication of the test results, it is recommended that all test reports should be collected by duly authorized person and not by the contractor/supplier.

Observation on Specimen(if any):

1.As the strength is below the desired design strength, so nec. measures to be taken as per particular specifications of contract.

Laboratory Technichian Test Performed By Vetted By

This is a computer genarated copy

No signature is required

Permissible Value:

1.

Note: [1 Mpa = 145 Psi, 1 kg/cm2 = 14.223 psi]