

MATERIAL TESTING LABORATORY

MILITARY ENGINEER SERVICES (MES) TEST RESULTS FOR FINENESS MODULUS (F.M.) OF SAND

Job No : 18/2021-2022(Sand).

Name of Client : GE (Army) South, Dhaka. Copy No : 02

Ref Itr No : 6000/Misc/15/E-6 Dt. 17 Aug'2021.

Project Name : CEA/513 of 2020-2021.

Sample Specimen : Local Sand.

Date of Sample Collection : Wednesday, 25 August, 2021

Sieve Size	Wt of Material Retained (gms)	Percentage Matarial Retained (rounded)	Cumulative % Retained	% Finer	Remarks
#4	0	0	0		
#8	0	0	0		
#16	0.46	0.12	0.12		
#30	3.17	0.79	0.91		
#50	254.25	63.56	64.47		FM = 1.61
#100	123.6	30.9	95.37		
#200	14.53	3.63			
Pan	2.77	0.69			
			$\Sigma = 160.86$		

Cautions:

- 1. Samples as supplied to the laboratory have been tested. The laboratory authority does not bear any responsibility as to the representative charecter of the samples to be tested.
- 2. It is recommended that the samples are sent in a secured and sealed cover/packet/container under signature of the competent authority.
- 3. In order to avoid fraudulent fabrication of the test results, it is recommended that all test reports should be collected by duly authorized person and not by the contractor/supplier.

Observation on Specimen(if any):

1.

2.

Laboratory Technichian Test Performed By Vetted By

This is a computer genarated copy

No signature is required

Permissible Value:

- 1.For Sylhet/Domar Sand minimum FM will be = 2.50
- 2.For Local Sand minimum FM will be = 1.50
- 3. For Vitty Sand minimum FM will be = 0.80