

MATERIAL TESTING LABORATORY

MILITARY ENGINEER SERVICES (MES) TEST RESULTS FOR FINENESS MODULUS (F.M.) OF SAND

Job No : 58/2021-2022(Sand).

Name of Client : GE (Air) Kurmitola, Dhaka. Copy No : 01

Ref Itr No : 6404/13/E-6 Dt. 03 Oct'2021. Project Name : CE Air/78 of 2020-2021.

Sample Specimen : Sylhet Sand.

Date of Sample Collection : Monday, 04 October, 2021

Sieve Size	Wt of Material Retained (gms)	Percentage Matarial Retained (rounded)	Cumulative % Retained	% Finer	Remarks
#4	3.75	0.94	0.94		
#8	17.4	4.35	5.29		
#16	85.64	21.41	26.7		
#30	213.3	53.33	80.02		
#50	66.42	16.61	96.63		FM = 3.09
#100	11.41	2.85	99.48		
#200	1.28	0.32	····		
Pan	0.3	0.08			
			$\Sigma = 309.05$		

Cautions:

- 1. Samples as supplied to the laboratory have been tested. The laboratory authority does not bear any responsibility as to the representative charecter of the samples to be tested.
- 2. It is recommended that the samples are sent in a secured and sealed cover/packet/container under signature of the competent authority.
- 3. In order to avoid fraudulent fabrication of the test results, it is recommended that all test reports should be collected by duly authorized person and not by the contractor/supplier.

Observation on Specimen(if any):

1.

2.

Laboratory Technichian Test Performed By Vetted By

This is a computer genarated copy

No signature is required

Permissible Value:

- 1.For Sylhet/Domar Sand minimum FM will be = 2.50
- 2.For Local Sand minimum FM will be = 1.50
- 3. For Vitty Sand minimum FM will be = 0.80