

MATERIAL TESTING LABORATORY MILITARY ENGINEER SERVICES (MES)

TEST RESULTS FOR TENSILE STRENGTH OF PLAIN/DEFORMED/RIBBED COLD TWISTED M.S. BARS

Job No
Name of Client
Ref Itr No
Project Name
Date of Collection

PDCAS/58 of 2020-2021/68/E-6 Dt. 14 Nov'2021.
PDCAS/58 of 2020-2021.

: Thursday, 18 November, 2021

: 137/2021-2022(Steel). : GE (Army) North, Dhaka.

Copy No.	
Sample Specimen	
Sample Grade	
Frog Mark	

: 02

: Length 600 mm Dia 16mm

: 60

: GPH B-500 CWR

Sample No	Nominal Dia	Actual Dia	Area Under Test	Actual Unit Weight	Average Actual Unit Weight	Yield or Proof Load	Yield or Proof Strength	Average Yield or Proof Strength	Ultimate Load	Ultimate Strength	Average Ultimate Strength	% (g	auge Elon gth) % (Elongation % (gauge length)		erage gation gauge gth)
	inch mm	inch mm	sq.inch sq.mm	lb/ft kg/m	lb/ft kg/m	lb kn	psi Mpa	psi Mpa	lb kn	psi Mpa	psi Mpa	8inch	5d**	8inch	5d**		
1	0.63 16	0.629 15.986	0.3116 201.0619	1.059 1.576		25576.63 113.77	82070 566		29674.92 132	95220 656		17.5					
2	0.63 16	0.629 15.986	0.3116 201.0619	1.059 1.576	1.059 1.576	25345.08 112.74	81327 561	81574 562	29758.1 132.37	95487 658	95511 658	18.5		18			
3	0.63 16	0.629 15.986	0.3116 201.0619	1.059 1.576		25345.08 112.74	81327 561		29863.76 132.84	95826 661		17.5					

Cautions:

1. Samples as supplied to the laboratory have been tested. The laboratory authority does not bear any responsibility as to the representative charecter of the samples to be tested.

2. It is recommended that the samples are sent in a secure and sealed cover/packet/container under signature of the competent authority.

3. In order to avoid fraudulent fabrication of the test results, it is recommended that all test reports should be collected by duly authorized person and not by the contractor/supplier.

Observation on Specimen(if any):

1.Diameter & Unit weight of 16 mm bar is less than the standard value but within tolerance limit according to MES Schedule of Rates-2016.

Minimu	m Standard	Requiremer	nts (BDS/ISO	Minimum Standard Requirments(ASTM A615/A616M-96a)										
6935-2:1991(E)				ASTM A 615 M			ASTM A 615 M			ASTM A 615/A 615 M				
Grade	Y/strength	Ult.Str	Elongation	Grade	Y/strength	Ult.Str	Grade	Y/strength	Ult.Str	Minimum Elongation in 8"(203.2 mm) GL (%)				
	N/mm2 or Mpa	N/mm2 or Mpa	%		psi (kg/cm2)	psi (kg/cm2)		Mpa (kg/cm2)	Mpa (kg/cm2)	10 mm	13,16,19 mm	22,25 mm	29,32,36 mm	
300	300	330	16	40	40000(2810)	70000(4910)	300	300(3050)	500(5090)	11	12		11	
400/400w	400	440	14	60	60000(4210)	90000(6310)	420	420(4275)	620(6295)	9	9	8	7	
500/500w	500	550	14	75	75000(5255)	100000(7015)	520	520(5275)	690(7010)		7	7	6	

Note :[1 Mpa = 145 Psi, 1 kg/cm2 = 14.223 psi] Laboratory Technichian

Test Performed By

Vetted By

This is a computer genarated copy No signature is required