

MATERIAL TESTING LABORATORY

MILITARY ENGINEER SERVICES (MES) TEST RESULTS FOR FINENESS MODULUS (F.M.) OF SAND

Job No : 08/2023-2024(Sand).

Name of Client : GE (Navy) Khulna. Copy No : 01

Ref Itr No : EinC/183 of 2022-2023/15/E-6 Dt.10 July'2023.

Project Name : Construction of 1 X Comflot Officer's residence (C/D type 2:2).

Sample Specimen : Sylhet sand.

Date of Sample Collection : Tuesday, 25 July, 2023

Sieve Size	Wt of Material Retained (gms)	Percentage Matarial Retained (rounded)	Cumulative % Retained	% Finer	Remarks
#4	10.82	2.71	2.71		
#8	39.13	9.78	12.49		
#16	115	28.75	41.24		
#30	141.7	35.43	76.66		
#50	72.21	18.05	94.72		FM = 3.27
#100	16.17	4.04	98.76		
#200	3.42	0.86			
Pan	1.23	0.31			
			$\Sigma = 326.57$		

Cautions:

- 1. Samples as supplied to the laboratory have been tested. The laboratory authority does not bear any responsibility as to the representative charecter of the samples to be tested.
- 2. It is recommended that the samples are sent in a secured and sealed cover/packet/container under signature of the competent authority.
- 3. In order to avoid fraudulent fabrication of the test results, it is recommended that all test reports should be collected by duly authorized person and not by the contractor/supplier.

Observation on Specimen(if any):

1.

2.

Laboratory Technichian Test Performed By Vetted By

This is a computer genarated copy

No signature is required

Permissible Value:

- 1.For Sylhet/Domar Sand minimum FM will be = 2.50
- 2.For Local Sand minimum FM will be = 1.50
- 3. For Vitty Sand minimum FM will be = 0.80